

. WELCON





Inheriting reliable performance and outstanding serviceability of GRG ATMs, the H22V series bulk cash dispensers are designed to optimize deployers' cost and enhance self-service satisfaction. GRGBanking's continuous innovation makes H22V series the unrivalled ATMs to meet the diverse and dynamic market requirements.

H22V Series Multi-function Cash Dispenser

Features

Outstanding capacity and reliability: Maximum bulk cash capacity enlarges by 67%, and dispensing cassette capacity by 17% comparing with other mainstream models in the market. Reliable performance maximizes machine uptime.

Advanced and secure solution: Newly integrated card-reader with comprehensive anti-skimming solutions, electromagnetic interference, and linkage alarm device that raises card security. PCI compliant EPP provides advanced account security for users.

Easy deployment and maintenance: Special carbon fiber composite and optimized mechanism ensures lighter weight and easier deployment of H22V series. Modular design and various ways of access largely enhances maintenance efficiency.

Specifications Controlling Unit

- IPC: Intel H61/H81/Q87,support Core i3/i5/i7 CPU, 1TB HHD, Max. 32GB memory, DVD-RW
- Windows® 7 /10

Cash Processing Unit

- High-speed bulk dispenser:
 Dispensing speed: 7 notes per second
 -Max. 100 notes per transaction
 -Up to 4 cassettes
- -Cassette capacity: max. 3,500 notes*
- Reject capacity: max. 300 notes
- Retract capacity: max. 300 notes
- OCR for note serial number recognition (opt.)
- RFID (opt.)

Customer Interfaces

- Display:
- -19" color vandal-resistive consumer display
- -Privacy filter (opt.)
- Keypad:
 -4*4 metal encryption PIN pad

- -Dust proof/water proof/vandal resistant
- -PCI compliant -EMV certified
- Card reader:
 - -Motorized card reader: Card return on power failure (opt.), Card retract (opt.) -DIP card reader (opt.)
 - -Anti-skimming design (opt.)
 - -Contactless smart card reader/writer (opt.)
- Receipt printer:
- -Graphic thermal receipt printer -Capture and retract capability (opt.)
- Journal printer (opt.):
- -High speed dot matrix journal printer -Thermal printer

Security

- Physical:
- -Mechanical combination lock -Electronic lock (opt.)
- PCI compliant EPP
- EMV Level 1 and Level 2 certified -Electro magnetic interference device
- Biometric Authentication: -Finger vein reader (opt.)

- -Finger print scanner (opt.) -Facial recognition (opt.)
- PIN Pad shield (opt.)
- Customer awareness mirror
- DVR surveillance system (opt.)
- Transaction image capture for surveillance (opt.)
- UPS (opt.)
- SecOne for software and network security (opt.)
- Sonic alarm modules (opt.)
- UL/CEN L/CEN 1/CEN IV Safe

Maintenance

- 10" LCD service panel with touch screen on TTW type
- Front, rear and side access

Working Environment

- Temperature: -Indoor: 32°F(0 °C) to 104°F(40°C); -Outdoor: -31°F(-35°C) to 122°F(50°C) (with optional heating unit)
- Relative humidity: 20% to 95% noncondensing

ltems		H22V	H22VL
Туре		Through-the-Wall	Lobby
Access		Rear	Front
Dimension (H*W*D) & Weight	Without UPS & DVR	UL Safe: 1716mm x 620mm x 1026mm, 490kg CEN L/CEN 1 Safe: 1716mm x 620mm x 1026mm, 515kg CEN IV Safe: 1716mm x 620mm x 1060mm, 650kg	UL Safe: 1489mm x 476mm x 855mm, 480kg CEN L/CEN 1 Safe: 1489mm x 476mm x 855mm, 505kg CEN IV Safe: 1492mm x 476mm x 855mm, 640kg
	With UPS & DVR	UL Safe: 1737mm x 620mm x 1026mm, 515kg CEN L/CEN 1 Safe: 1737mm x 620mm x 1026mm, 540kg CEN IV Safe: 1763mm x 620mm x 1060mm, 675kg	UL Safe: 1737mm x 476mm x 855mm, 505kg CEN L/CEN 1 Safe: 1737mm x 476mm x 855mm, 530kg CEN IV Safe: 1740mm x 476mm x 855mm, 665kg

*The actual capacity is subject to the thickness and fitness of local currency.















Authorized GRGBanking Re-Seller

Jeremiah O'Conner (415) 483-1524 | <u>sales@@mvpatm.com</u> <u>Click here</u> to schedule a meeting Specifications are subject to update without prior notice. Please consult GRGBanking or its representative for the latest information.

